

## TYRES

Product group	Tyres
Item number	10466466
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24



**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.

## Technical Informations

Item number	10466466
EAN	4040658089855
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	27,60
Recommended rim size	6.00
Permitted rim size	6.75, 7.50
Maximum air pressure [bar].	7,60
Section width (mm)	206
Outer diameter of tyre [mm].	752
Stat. radius (SLR) [mm]	352
Rolling circumference [mm].	2294
Tread depth (mm)	13,0

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 M	1600	130	Single	7,60	
122 M	1500	130	Twin	7,60	