

## TYRES

|                 |                    |
|-----------------|--------------------|
| Product group   | Tyres              |
| Item number     | 10466466           |
| Valid tyre size | 205 / 75 R 17.5    |
| LI / SI / PR    | 124 / 122 M, 14 PR |
| TL/TT           | TL                 |
| Brand           | Windpower          |
| Tread pattern   | WSR 24             |



**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.

## Technical Informations

|                              |                    |
|------------------------------|--------------------|
| Item number                  | 10466466           |
| EAN                          | 4040658089855      |
| Valid tyre size              | 205 / 75 R 17.5    |
| LI / SI / PR                 | 124 / 122 M, 14 PR |
| TL/TT                        | TL                 |
| Brand                        | Windpower          |
| Tread pattern                | WSR 24             |
| M+S                          | M+S                |
| 3PMSF                        | 3PMSF              |
| Axle position truck          | FA                 |
| Rolling resistance           | D                  |
| Wet grip                     | B                  |
| Rolling noise [db].          | 73                 |
| Rolling noise level          | B                  |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| ECE regulation number        | ECE 54,ECE 117     |
| Nettogewicht [kg] (gültig)   | 27,60              |
| Recommended rim size         | 6.00               |
| Permitted rim size           | 6.75, 7.50         |
| Maximum air pressure [bar].  | 7,60               |
| Section width (mm)           | 206                |
| Outer diameter of tyre [mm]. | 752                |
| Stat. radius (SLR) [mm]      | 352                |
| Rolling circumference [mm].  | 2294               |
| Tread depth (mm)             | 13,0               |

E-Ready

No

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 124 M | 1600               | 130          | Single        | 7,60                     |              |
| 122 M | 1500               | 130          | Twin          | 7,60                     |              |