

TYRES

Product group	Tyres
Item number	10466468
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	145 / 143 M (146 / 144 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

Technical Informations

Item number	10466468
EAN	4040658090660
Valid tyre size	285 / 70 R 19.5
LI / SI / PR	145 / 143 M (146 / 144 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	41,80
Recommended rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	280
Outer diameter of tyre [mm].	891
Stat. radius (SLR) [mm]	408
Rolling circumference [mm].	2718
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 M	2900	130	Single	8,30	
146 L	3000	120	Single	8,30	
143 M	2725	130	Twin	8,30	
144 L	2800	120	Twin	8,30	