

TYRES

Product group	Tyres
Item number	10466501
Valid tyre size	9 R 22.5
LI / SI / PR	136 / 134 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- The Windpower WSR 24 is a modern front axle and trailer tyre for local and distribution traffic.
- It provides excellent grip, even on wet road roads and has low rolling resistance.
- The tyre is particularly low-wearing due to its special tread pattern and is characterised by a long service life.

Technical Informations

Item number	10466501
EAN	4040658074363
Valid tyre size	9 R 22.5
LI / SI / PR	136 / 134 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 24
M+S	M+S
Axle position truck	FA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	42,70
Recommended rim size	6.75
Permitted rim size	6.00, 7.50
Maximum air pressure [bar].	8,30
Section width (mm)	228
Outer diameter of tyre [mm].	968
Rolling circumference [mm].	2952
Tread depth (mm)	14,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 M	2240	130	Single	8,30	
134 M	2120	130	Twin	8,30	