

TYRES

Product group	Tyres
Item number	10466502
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 75



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- The Windpower WSR 75 is a truck tyre for drive axles for use in local and regional transport.
- Its tread pattern drains water and prevents aquaplaning reliably.
- It is characterized by excellent handling on dry and wet roads.

Technical Informations

Item number	10466502
EAN	4040658097232
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 75
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	48,88
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	252
Outer diameter of tyre [mm].	1022
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	3117
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 M	2800	130	Single	9,00	
142 M	2650	130	Twin	9,00	