

TYRES

Product group	Tyres
Item number	10466504
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 L, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 08



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in demanding use with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10466504
EAN	4040658035296
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 L, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 08
M+S	M+S
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	76
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	48,60
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	258
Outer diameter of tyre [mm].	1025
Rolling circumference [mm].	3126
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 L	2800	120	Single	9,00	
142 L	2650	120	Twin	9,00	