

TYRES

Product group	Tyres
Item number	10466507
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 55



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- The Windpower WDR 55 is a truck tyre for drive axles for use in local transport.
- The tyre provides very good traction and driving stability.
- Due to its hard-wearing rubber compound, the tyre is protected against premature wear as well as against impact and collision damage.

Technical Informations

Item number	10466507
EAN	4040658094132
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 55
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	48,05
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	258
Outer diameter of tyre [mm].	1025
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	3126
Tread depth (mm)	15,5

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 M	2800	130	Single	9,00	
142 M	2650	130	Twin	9,00	