

TYRES

Product group	Tyres
Item number	10466508
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Drive tread pattern for individual local and mixed use.
- High degree of adhesion and traction with low operating costs.
- Increased resilience against penetration and impact damages.

Technical Informations

Item number	10466508
EAN	4040658035319
Valid tyre size	10 R 22.5
LI / SI / PR	144 / 142 M, 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	48,20
Recommended rim size	7.50
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	258
Outer diameter of tyre [mm].	1025
Rolling circumference [mm].	3126
Tread depth (mm)	15,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 M	2800	130	Single	9,00	
142 M	2650	130	Twin	9,00	