

TYRES

Product group	Tyres
Item number	10466515
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 L (148 / 145 K), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10466515
EAN	4040658089718
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 L (148 / 145 K), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,20
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	281
Outer diameter of tyre [mm].	1054
Stat. radius (SLR) [mm]	492
Rolling circumference [mm].	3215
Tread depth (mm)	17,0

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 L	3000	120	Single	8,30	
148 K	3150	110	Single	8,30	
143 L	2725	120	Twin	8,30	
145 K	2900	110	Twin	8,30	