

TYRES

Product group	Tyres
Item number	10466517
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 L (148 / 145 K), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre for the drive axle (especially for construction vehicles).
- Extra-deep lug profile (20 mm) with cut-and tear-proof rubber compound.
- Excellent water displacement due to open tyre shoulder design.

Technical Informations

Item number	10466517
EAN	4040658097249
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 L (148 / 145 K), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	62,76
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	281
Outer diameter of tyre [mm].	1066
Stat. radius (SLR) [mm]	498
Rolling circumference [mm].	3251
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 L	3000	120	Single	8,30	
148 K	3150	110	Single	8,30	
143 L	2725	120	Twin	8,30	
145 K	2900	110	Twin	8,30	