

## **TYRES**

Product group	Tyres	
Item number	10466518	
Valid tyre size	11 R 22.5	
LI / SI / PR	148 / 145 J, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WGB 20	





## Notes and features

- Modern bus tyre with protecting rib for all-year use.
- More efficient fuel consumption due to reduced rolling resistance.
- Long service life and even wear.



## **Technical Informations**

Item number	10466518
EAN	4040658055669
Valid tyre size	11 R 22.5
LI / SI / PR	148 / 145 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGB 20
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	С
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	62,20
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	284
Outer diameter of tyre [mm].	1062
Rolling circumference [mm].	3239
Tread depth (mm)	20,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 J	3150	100	Single	8,30	
145 J	2900	100	Twin	8,30	