

TYRES

Product group	Tyres
Item number	10466519
Valid tyre size	13 R 22.5
LI / SI / PR	154 / 151 K (156 / 150 G), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Construction site tyre for the drive axle (especially for construction vehicles).
- Extra-deep lug profile (20 mm) with cut-and tear-proof rubber compound.
- Excellent water displacement due to open tyre shoulder design.

Technical Informations

Item number	10466519
EAN	4040658094163
Valid tyre size	13 R 22.5
LI / SI / PR	154 / 151 K (156 / 150 G), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	73,07
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	8,30
Section width (mm)	319
Outer diameter of tyre [mm].	1129
Stat. radius (SLR) [mm]	527
Rolling circumference [mm].	3443
Tread depth (mm)	20,6

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 K	3750	110	Single	8,30	
156 G	4000	90	Single	8,30	
151 K	3450	110	Twin	8,30	
150 G	3350	90	Twin	8,30	