

TYRES

Product group	Tyres
Item number	10466521
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 M (148 / 145 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 37



Bohnenkamp
Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- Drive tread pattern for local and regional transport.
- The WDR 37 pattern is a further development of the WDR36 and HN355 tread patterns and combines the best features of these two predecessors in a single tread pattern.
- It provides a high degree of adhesion and traction with low fuel consumption.
- The special tread pattern ensures even wear and high mileage.
- Its optimal rubber compound and robust shoulder design provide increased resilience against collision, impact and other types of damage.
- M+S marking and snowflake symbol (3PMSF).
- Retreadable casing.

Technical Informations

Item number	10466521
EAN	4040658072680
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 M (148 / 145 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 37
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	62,60
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	276
Outer diameter of tyre [mm].	1068
Stat. radius (SLR) [mm]	498
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 M	3000	130	Single	8,30	
148 L	3150	120	Single	8,30	
143 M	2725	130	Twin	8,30	
145 L	2900	120	Twin	8,30	