

## TYRES

Product group	Tyres
Item number	10466524
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 M (148 / 145 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

## Technical Informations

Item number	10466524
EAN	4040658089749
Valid tyre size	11 R 22.5
LI / SI / PR	146 / 143 M (148 / 145 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	56,90
Recommended rim size	8.25
Permitted rim size	7.50
Maximum air pressure [bar].	8,30
Section width (mm)	277
Outer diameter of tyre [mm].	1051
Stat. radius (SLR) [mm]	492
Rolling circumference [mm].	3206
Tread depth (mm)	15,0

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 M	3000	130	Single	8,30	
148 L	3150	120	Single	8,30	
143 M	2725	130	Twin	8,30	
145 L	2900	120	Twin	8,30	