

## TYRES

Product group	Tyres
Item number	10466533
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER**  
Get Your Job Done

## Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

## Technical Informations

Item number	10466533
EAN	4040658089848
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	62,10
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,30
Section width (mm)	298
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	504
Rolling circumference [mm].	3270
Tread depth (mm)	16,5

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	9,30	
149 M	3250	130	Twin	9,30	