

TYRES

Product group	Tyres
Item number	10466537
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Drive tread pattern for individual local and mixed use.
- High degree of adhesion and traction with low operating costs.
- Increased resilience against penetration and impact damages.

Technical Informations

Item number	10466537
EAN	4040658001024
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	69,10
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,30
Section width (mm)	299
Outer diameter of tyre [mm].	1091
Stat. radius (SLR) [mm]	504
Rolling circumference [mm].	3328
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	9,30	
149 M	3250	130	Twin	9,30	