

TYRES

Product group	Tyres
Item number	10466539
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- All-position tyre for mixed use.
- High resistance in tough operations with robust tyre shoulder.
- Reduced heat generation.
- Retreadable casing.

Technical Informations

Item number	10466539
EAN	4040658066436
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 08
M+S	M+S
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	65,10
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,30
Section width (mm)	303
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	504
Rolling circumference [mm].	3282
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,30	
149 L	3250	120	Twin	9,30	