

TYRES

Product group	Tyres
Item number	10466546
Valid tyre size	13 R 22.5
LI / SI / PR	154 / 151 K (156 / 150 G), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 353



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Construction site tyre for the drive axle (especially for construction vehicles).
- Extra-deep lug profile (20 mm) with cut-and tear-proof rubber compound.
- Excellent water displacement due to open tyre shoulder design.

Technical Informations

Item number	10466546
EAN	4040658001055
Valid tyre size	13 R 22.5
LI / SI / PR	154 / 151 K (156 / 150 G), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 353
M+S	M+S
Axle position truck	RA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	75,10
Maximum air pressure [bar].	8,30
Section width (mm)	319
Outer diameter of tyre [mm].	1129
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3443
Tread depth (mm)	20,6
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 K	3750	110		8,30	
156 G	4000	90		8,30	
151 K	3450	110		8,30	
150 G	3350	90		8,30	