

TYRES

Product group	Tyres	
Item number	10466554	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 149 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDR 37	





Notes and features

- Drive tread pattern for local and regional transport.
- The WDR 37 pattern is a further development of the WDR36 and HN355 tread patterns and combines the best features of these two predecessors in a single tread pattern.
- It provides a high degree of adhesion and traction with low fuel consumption.
- The special tread pattern ensures even wear and high mileage.
- Its optimal rubber compound and robust shoulder design provide increased resilience against collision, impact and other types of damage.
- M+S marking and snowflake symbol (3PMSF).
- Retreadable casing.



Technical Informations

Item number	10466554
EAN	4040658072741
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 37
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	Е
Wet grip	С
Rolling noise [db].	75
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	67,20
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	296
Outer diameter of tyre [mm].	1062
Rolling circumference [mm].	3239
Tread depth (mm)	22,5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	9,00	
149 M	3250	130	Twin	9,00	