Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10466556	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	152 / 149 L, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDW 80	





Notes and features

- Winter drive wheel tyre with reliable grip and traction. .
- Extra-wide, deep tread pattern bed / open tyre shoulder.
- Excellent self-cleaning properties.

- Tread compound adapted to winter use. •
- Reduced operating costs due to long-life compound.
- Retreadable casing.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10466556
EAN	4040658058882
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDW 80
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	F
Wet grip	C
Rolling noise [db].	76
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	71,30
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	298
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3239
Tread depth (mm)	24,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
149 L	3250	120	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.