# Bohnenkamp Moving Professionals

05.02.2025

### TYRES

Product group	Tyres	
Item number	10466557	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	154 / 149 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 36	





#### Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number 10466557   EAN 4040658052989   Valid tyre size 295 / 80 R 22.5	
Valid tyre size 295 / 80 R 22.5	
LI / SI / PR 154 / 149 M, 18 PR	
TL/TT TL	
Brand Windpower	
Tread pattern WSR 36	
M+S M+S	
Axle position truck FA	
Rolling resistance D	
Wet grip C	
Rolling noise [db]. 73	
Antistatic No	
Tyre colour Black	
ECE regulation number ECE 54,ECE 117	
Nettogewicht [kg] (gültig) 59,90	
Recommended rim size 9.00	
Permitted rim size 8.25	
Maximum air pressure [bar]. 9,00	
Section width (mm) 302	
Outer diameter of tyre [mm]. 1046	
Stat. radius (SLR) [mm] 490	
Rolling circumference [mm]. 3190	
E-Ready No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
149 M	3250	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.