

TYRES

Product group	Tyres
Item number	10466563
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 227



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Modern steering axle tyre of the newest generation for long-haul transport.
- Safe and quiet handling on wet and dry roads.
- Optimised running smoothness and tracking due to more transverse sipes.
- Increased braking force.

Technical Informations

Item number	10466563
EAN	4040658001109
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 227
M+S	M+S
Axle position truck	FA
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	55,20
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	315
Outer diameter of tyre [mm].	943
Rolling circumference [mm].	2876
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	