

TYRES

Product group	Tyres
Item number	10466566
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 150 M
TL/TT	TL
Brand	Windpower
Tread pattern	HN 257



Notes and features

- Modern front axle tyre for local and distribution traffic.
- Optimised and safe handling.

• Stone-repellent sipe in the tread base.



Technical Informations

Item number	10466566
EAN	4040658001130
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 150 M
TL/TT	TL
Brand	Windpower
Tread pattern	HN 257
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	С
Rolling noise [db].	76
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	67,00
Maximum air pressure [bar].	8,30
Section width (mm)	315
Outer diameter of tyre [mm].	1080
Rolling circumference [mm].	3294
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130		8,30	
150 M	3350	130			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.