# Bohnenkamp Moving Professionals

05.02.2025

### TYRES

| Product group   | Tyres           |
|-----------------|-----------------|
| Item number     | 10466568        |
| Valid tyre size | 315 / 70 R 22.5 |
| LI / SI / PR    | 152 / 148 M     |
| TL/TT           | TL              |
| Brand           | Windpower       |
| Tread pattern   | HN 355          |





#### Notes and features

- Drive tread pattern for individual local and mixed use.
- High degree of adhesion and traction with low operating costs.
- Increased resilience against penetration and impact damages.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

| Item number                  | 10466568        |
|------------------------------|-----------------|
| EAN                          | 4040658001154   |
| Valid tyre size              | 315 / 70 R 22.5 |
| LI / SI / PR                 | 152 / 148 M     |
| TL/TT                        | TL              |
| Brand                        | Windpower       |
| Tread pattern                | HN 355          |
| 3PMSF                        | 3PMSF           |
| Axle position truck          | RA              |
| Rolling resistance           | D               |
| Wet grip                     | С               |
| Rolling noise [db].          | 73              |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 54,ECE 117  |
| Nettogewicht [kg] (gültig)   | 65,20           |
| Maximum air pressure [bar].  | 8,30            |
| Section width (mm)           | 312             |
| Outer diameter of tyre [mm]. | 1030            |
| Tread depth (mm)             | 23,0            |
| E-Ready                      | No              |

### Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 152 M | 3550               | 130          |               | 8,30                        |              |
| 148 M | 3150               | 130          |               |                             |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.