

TYRES

Product group	Tyres	
Item number	10466577	
Valid tyre size	315 / 80 R 22.5	
LI / SI / PR	154 / 150 M	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 36	





Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.



Technical Informations

Item number	10466577
EAN	4040658053023
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 150 M
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 36
Axle position truck	FA
Rolling resistance	В
Wet grip	В
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	68,40
Maximum air pressure [bar].	8,30
Section width (mm)	315
Outer diameter of tyre [mm].	1080
Rolling circumference [mm].	3294
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130		8,30	
150 M	3350	130			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.