

## TYRES

Product group	Tyres
Item number	10466591
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	158 L (160 K), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



**WINDPOWER**  
*Get Your Job Done*

## Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

## Technical Informations

Item number	10466591
EAN	4040658055409
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	158 L (160 K), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	73,10
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	384
Outer diameter of tyre [mm].	1005
Stat. radius (SLR) [mm]	463
Rolling circumference [mm].	3065
Tread depth (mm)	17,0

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,00	
160 K	4500	110	Single	9,00	