

TYRES

Product group	Tyres
Item number	10466597
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	158 L (160 K)
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466597
EAN	4040658001284
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	158 L (160 K)
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	75,90
Maximum air pressure [bar].	8,30
Section width (mm)	385
Outer diameter of tyre [mm].	1070
Rolling circumference [mm].	3242
Tread depth (mm)	16,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120		8,30	
160 K	4500	110			