Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	10466604	
Valid tyre size	255 / 70 R 22.5	
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WSR 36	





Notes and features

- Steer axle tyre of the newest generation for local and regional transport.
- Optimised handling on dry and wet roads.
- Improved water displacement.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10466604		
EAN	4040658059179		
Valid tyre size	255 / 70 R 22.5		
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WSR 36		
M+S	M+S		
Axle position truck	FA		
Rolling resistance	C		
Wet grip	C		
Rolling noise [db].	73		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	42,30		
Recommended rim size	7.50		
Permitted rim size	8.25		
Maximum air pressure [bar].	8,30		
Section width (mm)	249		
Outer diameter of tyre [mm].	928		
Stat. radius (SLR) [mm]	433		
Rolling circumference [mm].	2830		
Tread depth (mm)	14,5		
E-Ready	No		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130	Single	8,30	
140 L	2500	120	Single	8,30	
137 M	2300	130	Twin	8,30	
140 L	2500	120	Twin	8,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.