

TYRES

Product group	Tyres
Item number	10466607
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466607
EAN	4040658055720
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	48,80
Recommended rim size	8.25
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	274
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	455
Rolling circumference [mm].	2955
Tread depth (mm)	17,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 M	3150	130	Single	9,00	
145 M	2900	130	Twin	9,00	