

TYRES

Product group	Tyres
Item number	10466612
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Drive tread pattern for individual local and mixed use.
- High degree of adhesion and traction with low operating costs.
- Increased resilience against penetration and impact damages.

Technical Informations

Item number	10466612
EAN	4040658001369
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	HN 355
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	50,60
Recommended rim size	8.25
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	274
Outer diameter of tyre [mm].	975
Stat. radius (SLR) [mm]	454
Rolling circumference [mm].	2974
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 M	3150	130	Single	9,00	
145 M	2900	130	Twin	9,00	