

TYRES

Product group	Tyres
Item number	10466613
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 J (152 / 148 E), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGB 20



WINDPOWER·TYRE
Get Your Job Done

Notes and features

- Modern bus tyre with protecting rib for all-year use.
- More efficient fuel consumption due to reduced rolling resistance.
- Long service life and even wear.

Technical Informations

Item number	10466613
EAN	4040658055416
Valid tyre size	275 / 70 R 22.5
LI / SI / PR	148 / 145 J (152 / 148 E), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGB 20
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	51,00
Recommended rim size	8.25
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	273
Outer diameter of tyre [mm].	975
Rolling circumference [mm].	2974
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 J	3150	100	Single	9,00	
152 E	3550	70	Single	9,00	
145 J	2900	100	Twin	9,00	
148 E	3150	70	Twin	9,00	