

## **TYRES**

Product group	Tyres	
Item number	10466614	
Valid tyre size	tyre size 315 / 70 R 22.5	
LI / SI / PR	152 / 148 M (154 / 150 L), 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WDR 37	





## Notes and features

- Drive tread pattern for local and regional transport.
- The WDR 37 pattern is a further development of the WDR36 and HN355 tread patterns and combines the best features of these two predecessors in a single tread pattern.
- It provides a high degree of adhesion and traction with low fuel consumption.
- The special tread pattern ensures even wear and high mileage
- Its optimal rubber compound and robust shoulder design provide increased resilience against collision, impact and other types of damage.
- M+S marking and snowflake symbol (3PMSF).
- Retreadable casing.



## **Technical Informations**

Item number	10466614		
EAN	4040658072758		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	152 / 148 M (154 / 150 L), 18 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WDR 37		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	RA		
Rolling resistance	D		
Wet grip	С		
Rolling noise [db].	75		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 54,ECE 117		
Nettogewicht [kg] (gültig)	66,60		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	8,30		
Section width (mm)	315		
Outer diameter of tyre [mm].	1030		
Stat. radius (SLR) [mm]	480		
Rolling circumference [mm].	3142		
Tread depth (mm)	23,0		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	8,30	
154 L	3750	120	Single	8,30	
148 M	3150	130	Twin	8,30	
150 L	3350	120	Twin	8,30	