

TYRES

Product group	Tyres
Item number	10466617
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	158 L (160 J), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69



WINDPOWER
Get Your Job Done

Notes and features

- Modern, multifunctional trailer tyre for local, regional and long-distance transport.
- Long-life compound, flexible tread pattern for a long service life.
- Reinforced, wide tyre shoulder.

Technical Informations

Item number	10466617
EAN	4040658087929
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	158 L (160 J), 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WTR 69
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	73,80
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	8,30
Section width (mm)	381
Outer diameter of tyre [mm].	1008
Stat. radius (SLR) [mm]	499
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3074

Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	8,30	
160 J	4500	100	Single	8,30	