

TYRES

Product group	Tyres
Item number	10466618
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 55



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER·TYRE
Get Your Job Done

Notes and features

- The Windpower WDR 55 is a truck tyre for drive axles for use in local transport.
- The tyre provides very good traction and driving stability.
- Due to its hard-wearing rubber compound, the tyre is protected against premature wear as well as against impact and collision damage.

Technical Informations

Item number	10466618
EAN	4040658094149
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 55
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	44,29
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	254
Outer diameter of tyre [mm].	936
Stat. radius (SLR) [mm]	439
Rolling circumference [mm].	2855
Tread depth (mm)	20,0

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130	Single	8,30	
140 L	2500	120	Single	8,30	
137 M	2300	130	Twin	8,30	
140 L	2500	120	Twin	8,30	