

TYRES

Product group	Tyres
Item number	10466624
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	149 / 146 L (150 / 147 K), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDL 60



WINDPOWER
Get Your Job Done

Notes and features

- Latest-generation, modern drive wheel tyre for long-haul trucking.
- More efficient fuel consumption due to reduced rolling resistance.
- Reduced operating costs due to long-life compound.

Technical Informations

Item number	10466624
EAN	4040658084249
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	149 / 146 L (150 / 147 K), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDL 60
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	53,60
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	288
Outer diameter of tyre [mm].	926
Stat. radius (SLR) [mm]	433
Rolling circumference [mm].	2824
Tread depth (mm)	18,0

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 L	3250	120	Single	9,00	
150 K	3350	110	Single	9,00	
146 L	3000	120	Twin	9,00	
147 K	3075	110	Twin	9,00	