

TYRES

Product group	Tyres	
Item number	10466631	
Valid tyre size	295 / 80 R 22.5 152 / 149 J, 18 PR TL	
LI / SI / PR		
TL/TT		
Brand	Windpower	
Tread pattern	PRO GU01	





Technical Informations

Item number	10466631
EAN	4040658097256
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 149 J, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO GU01
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	С

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	С
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	67,17
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	310
Outer diameter of tyre [mm].	1063
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3242
Tread depth (mm)	19,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 J	3550	100	Single	9,00	
149 J	3250	100	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.