

## **TYRES**

Product group	Tyres	
Item number	10466632	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	154 / 149 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	PRO SR80	





## **Technical Informations**

Item number	10466632
EAN	4040658097263
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO SR80
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	В
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	65,88
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	310
Outer diameter of tyre [mm].	1057
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3224
Tread depth (mm)	16,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
149 M	3250	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.