

## TYRES

Product group	Tyres
Item number	10466632
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO SR80



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER-TYRE**  
*Get Your Job Done*

## Technical Informations

Item number	10466632
EAN	4040658097263
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	154 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO SR80
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	D

Wet grip	B
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	65,88
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	310
Outer diameter of tyre [mm].	1057
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3224
Tread depth (mm)	16,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
149 M	3250	130	Twin	9,00	