Bohnenkamp Moving Professionals

13.03.2025

TYRES

Product group	Tyres	
Item number	10466632	
Valid tyre size	295 / 80 R 22.5	
LI / SI / PR	154 / 149 M, 18 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	PRO SR80	





Item number 10466632 EAN 4040658097263 Valid tyre size 295 / 80 R 22.5 LI / SI / PR 154 / 149 M, 18 PR TL/TT ΤL Brand Windpower **Tread pattern** PRO SR80 M+S M+S 3PMSF 3PMSF Axle position truck FA D **Rolling resistance**

Technical Informations

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Wet grip	В
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	65,88
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,00
Section width (mm)	310
Outer diameter of tyre [mm].	1057
Stat. radius (SLR) [mm]	490
Rolling circumference [mm].	3224
Tread depth (mm)	16,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
149 M	3250	130	Twin	9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.