

TYRES

Product group	Tyres	
Item number	10466634	
Valid tyre size	255 / 70 R 22.5	
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	WGC 28	





Notes and features

- Construction site tyre of the newest generation for drive axles
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.



Technical Informations

Item number	10466634		
EAN	4040658097379		
Valid tyre size	255 / 70 R 22.5		
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR		
TL/TT	TL		
Brand	Windpower		
Tread pattern	WGC 28		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA/RA/TR		
Rolling resistance	Е		
Wet grip	В		
Rolling noise [db].	74		
Rolling noise level	В		
Antistatic	No		
Tyre colour	Black		
Nettogewicht [kg] (gültig)	42,46		
Recommended rim size	7.50		
Permitted rim size	8.25		
Maximum air pressure [bar].	8,30		
Section width (mm)	254		
Outer diameter of tyre [mm].	932		
Stat. radius (SLR) [mm]	405		
Rolling circumference [mm].	2843		
Tread depth (mm)	17,5		
E-Ready	No		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130		8,30	
140 L	2500	120		8,30	
137 M	2300	130		8,30	
140 L	2500	120		8,30	