

TYRES

Product group	Tyres
Item number	10466634
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

Technical Informations

Item number	10466634
EAN	4040658097379
Valid tyre size	255 / 70 R 22.5
LI / SI / PR	140 / 137 M (140 / 140 L), 16 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	42,46
Recommended rim size	7.50
Permitted rim size	8.25
Maximum air pressure [bar].	8,30
Section width (mm)	254
Outer diameter of tyre [mm].	932
Stat. radius (SLR) [mm]	405
Rolling circumference [mm].	2843
Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 M	2500	130		8,30	
140 L	2500	120		8,30	
137 M	2300	130		8,30	
140 L	2500	120		8,30	