

TYRES

Product group	Tyres
Item number	10466635
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 K (149 / 146 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 75



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- The Windpower WSR 75 is a truck tyre for drive axles for use in local and regional transport.
- Its tread pattern drains water and prevents aquaplaning reliably.
- It is characterized by excellent handling on dry and wet roads.

Technical Informations

Item number	10466635
EAN	4040658097386
Valid tyre size	295 / 60 R 22.5
LI / SI / PR	150 / 147 K (149 / 146 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WSR 75
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,55
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	292
Outer diameter of tyre [mm].	920
Stat. radius (SLR) [mm]	428
Rolling circumference [mm].	2806
Tread depth (mm)	15,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 K	3350	110	Single	9,00	
149 L	3250	120	Single	9,00	
147 K	3075	110	Twin	9,00	
146 L	3000	120	Twin	9,00	