

TYRES

Product group	Tyres
Item number	10466636
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 76 II



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- The Windpower WDR 76 II is a truck tyre for drive axles for use in local transport.
- The tyre is designed with a high-quality new ply structure for demanding use.
- The reinforced bead with reinforced core increases robustness and resistance.
- The new 3-ply structure in the carcass (SATT) ensures optimum ride comfort.

Technical Informations

Item number	10466636
EAN	4040658097393
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 M, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDR 76 II
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	72,53
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,30
Section width (mm)	300
Outer diameter of tyre [mm].	1087
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3315
Tread depth (mm)	22,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	9,30	
149 M	3250	130	Twin	9,30	