

TYRES

Product group	Tyres
Item number	10466637
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53



WINDPOWER
Get Your Job Done

Notes and features

- Construction site tyre for the drive axle (especially for construction vehicles).
- Extra-deep lug profile (20 mm) with cut-and tear-proof rubber compound.
- Excellent water displacement due to open tyre shoulder design.

Technical Informations

Item number	10466637
EAN	4040658097409
Valid tyre size	12 R 22.5
LI / SI / PR	152 / 149 L, 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WDC 53
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	59,76
Recommended rim size	9.00
Permitted rim size	8.25
Maximum air pressure [bar].	9,30
Section width (mm)	301
Outer diameter of tyre [mm].	1081
Stat. radius (SLR) [mm]	507
Rolling circumference [mm].	3297
Tread depth (mm)	19,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,30	
149 L	3250	120	Twin	9,30	