

TYRES

Product group	Tyres
Item number	10466640
Valid tyre size	13 R 22.5
LI / SI / PR	156 / 150 K (154 / 151 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO GC72



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Notes and features

- The Windpower PRO GC72 is an all-position truck tyre for construction site vehicles in on- and off-road use.
- Its robust, strong side wall protects the tyre from side impacts.
- Zigzag-shaped circumferential and wide transverse grooves offer very good grip and traction on all surfaces.
- The special rubber compound under the tread ensures low heat development and driving safety.
- The optimum tread depth and the higher under-tread layer under the tread surface ensure a long service life and prevent damage to the carcass.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.

Technical Informations

Item number	10466640
EAN	4040658097430
Valid tyre size	13 R 22.5
LI / SI / PR	156 / 150 K (154 / 151 L), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO GC72
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	73,25
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	8,75
Section width (mm)	318
Outer diameter of tyre [mm].	1125
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3431
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 K	4000	110	Single	8,75	
154 L	3750	120	Single	8,75	
150 K	3350	110	Twin	8,75	
151 L	3450	120	Twin	8,75	