

TYRES

Product group	Tyres	
Item number	10466645	
Valid tyre size	315 / 60 R 22.5	
LI / SI / PR	152 / 148 L, 20 PR	
TL/TT	TL	
Brand	Windpower	
Tread pattern	PRO DL96	





Notes and features

- The Windpower PRO DL96 is a truck tyre for the drive axle for long-distance transport on well-maintained roads.
- Its tread pattern with longitudinal and transverse grooves offers very good grip and excellent braking and acceleration behaviour.
- Its two-layer high-quality silica rubber compound (Dual-Layer Technology) ensures low rolling resistance and low fuel consumption.



Technical Informations

Item number	10466645
EAN	4040658097270
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DL96
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	В
Wet grip	D
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	58,93
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	317
Outer diameter of tyre [mm].	954
Stat. radius (SLR) [mm]	446
Rolling circumference [mm].	2910
Tread depth (mm)	18,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	