

## TYRES

Product group	Tyres
Item number	10466646
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	154 / 148 L, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO SL91



Bohnenkamp  
■ ■ ● Moving Professionals

**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- The Windpower PRO SL91 is a steer axle tyre for long-distance driving on well-maintained roads.
- The design of the tyre shoulder and the even pressure distribution ensure even and slow wear and high mileage.
- The zigzag-shaped circumferential groove in the center of the tread ejects stones and thus prevents tyre damage.
- Straight circumferential grooves on the outside of the tread ensure outstanding performance at high speeds.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.

## Technical Informations

Item number	10466646
EAN	4040658097287
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	154 / 148 L, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO SL91
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	54,53
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	316
Outer diameter of tyre [mm].	942
Stat. radius (SLR) [mm]	478
Rolling circumference [mm].	2873
Tread depth (mm)	12,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
148 L	3150	120	Twin	9,00	