

TYRES

Product group	Tyres
Item number	10466650
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR85



Bohnenkamp
■ ■ ● Moving Professionals

WINDPOWER
Get Your Job Done

Technical Informations

Item number	10466650
EAN	4040658097317
Valid tyre size	315 / 70 R 22.5
LI / SI / PR	154 / 150 L (152 / 148 M), 18 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR85
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	C

Wet grip	C
Rolling noise [db].	73
Rolling noise level	A
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	66,06
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	9,00
Section width (mm)	314
Outer diameter of tyre [mm].	1024
Stat. radius (SLR) [mm]	477
Rolling circumference [mm].	3123
Tread depth (mm)	21,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 L	3750	120	Single	9,00	
152 M	3550	130	Single	9,00	
150 L	3350	120	Twin	9,00	
148 M	3150	130	Twin	9,00	