

## TYRES

Product group	Tyres
Item number	10466681
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28



**WINDPOWER**  
*Get Your Job Done*

## Notes and features

- Construction site tyre of the newest generation for drive axles.
- Strong hexagonal tread for excellent traction on tough terrain.
- Reinforced casing to protect against cuts and tread separation.
- Very good self-cleaning properties.

## Technical Informations

Item number	10466681
EAN	4040658055423
Valid tyre size	425 / 65 R 22.5
LI / SI / PR	165 K, 20 PR
TL/TT	TL
Brand	Windpower
Tread pattern	WGC 28
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	C
Wet grip	C
Rolling noise [db].	74
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	87,90
Recommended rim size	13.00
Permitted rim size	12.25
Maximum air pressure [bar].	8,30
Section width (mm)	421
Outer diameter of tyre [mm].	1121
Stat. radius (SLR) [mm]	519
Rolling circumference [mm].	3419
Tread depth (mm)	16,5

E-Ready

No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 K	5150	110	Single	8,30	