

## TYRES

|                 |                 |
|-----------------|-----------------|
| Product group   | Tyres           |
| Item number     | 10466690        |
| Valid tyre size | 435 / 50 R 19.5 |
| LI / SI / PR    | 160 J, 20 PR    |
| TL/TT           | TL              |
| Brand           | Windpower       |
| Tread pattern   | PRO TL98        |



**WINDPOWER·TYRE**  
*Get Your Job Done*

## Notes and features

- The Windpower PRO TL98 is a truck tyre for the trailer axle for use in long-distance transport.
- Its optimised tread design ensures slow wear and a long service life.
- The special reinforced bead construction with steel core (BWC = Bead Wrapped Chafer) protects the tyre from lateral impact damage even under difficult load conditions.
- Particularly high-quality, extremely strong cord plies (SHT = Super High Tensile Cord) ensure excellent handling and low rolling resistance.
- All tyres in the Pro Series are equipped with dual-layer technology, in which an outer and an underlying rubber layer complement each other perfectly.

## Technical Informations

|                              |                 |
|------------------------------|-----------------|
| Item number                  | 10466690        |
| EAN                          | 4040658097331   |
| Valid tyre size              | 435 / 50 R 19.5 |
| LI / SI / PR                 | 160 J, 20 PR    |
| TL/TT                        | TL              |
| Brand                        | Windpower       |
| Tread pattern                | PRO TL98        |
| M+S                          | M+S             |
| 3PMSF                        | 3PMSF           |
| Axle position truck          | TR              |
| Rolling resistance           | C               |
| Wet grip                     | B               |
| Rolling noise [db].          | 73              |
| Rolling noise level          | B               |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| Nettogewicht [kg] (gültig)   | 66,38           |
| Recommended rim size         | 14.00           |
| Maximum air pressure [bar].  | 9,00            |
| Section width (mm)           | 430             |
| Outer diameter of tyre [mm]. | 920             |
| Stat. radius (SLR) [mm]      | 428             |
| Rolling circumference [mm].  | 2806            |
| Tread depth (mm)             | 12,0            |
| E-Ready                      | No              |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 J | 4500               | 100          | Single        | 9,00                     |              |